

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
17 April 2003 (17.04.2003)

PCT

(10) International Publication Number
WO 03/031345 A1

(51) International Patent Classification⁷: **C02F 1/467**,
1/461

(21) International Application Number: PCT/GR02/00053

(22) International Filing Date: 10 October 2002 (10.10.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
20010100469 11 October 2001 (11.10.2001) GR

(71) Applicant and

(72) Inventor: NINOLAKIS, Markos [GR/GR]; 19 Riga Fer-
eou Str, GR-166 73 Voula Attikis (GR).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,

GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,
SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK,
TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: ELECTROCHEMICAL METHOD FOR WET OXIDATION-STERILIZATION OF LIQUID WASTE FROM FISH
SLAUGHTERING



(57) Abstract: Electrochemical method for wet oxidation-sterilization of liquid wastes from fish slaughtering where the pass of wastewaters is controlled by grid, controlled voltage and intensity of electric direct current, controlled conciseness of sodium chloride in the wastewaters, controlled temperature of the liquids wastes during electrolysis, controlled value of pH during electrolysis and elimination of residual oxidants with sodium sulfite or sulfur dioxide, I achieve the total elimination of all pathogens and in the same time reduce of the BOD₅, COD, Color and TSS in such a limits as by the law.



WO 03/031345 A1

ELECTROCHEMICAL METHOD FOR WET OXIDATION-STERILIZATION OF LIQUID WASTE FROM FISH SLAUGHTERING

5 TECHNICAL FIELD

The invention refers to the electrochemical method for wet oxidation-sterilization of the liquid wastes from fish slaughtering.

10 LEVEL OF CONVECTIONAL TECHNOLOGY

Up to now the disposal of liquid waste from fish slaughtering is achieved with biological treatment. The efficiency of such a process depend on the sudden increase or decrease of the organic load in the waste, it is
15 vulnerable to weather conditions, the result of the process is not steady and rarely with in the law, the disinfection that is completed in the last stage do not have the power to eliminate all the pathogen and creates during it's operation mud which is a huge environmental problem. The running cost of such a process is high.

20 ADVANTAGES OF THE INVENTION

The method, due to the production of powerful oxidants during electrolysis, such as O_2 , Cl_2 , ClO_2 , O_3 , O_2 , H_2O_2 , $[OH]$, $[CLOH]$ $[O]$
25 successfully oxidize all organics in the waste mass, no mud is created, it does not depend on any outer effects such as climate conditions and the running cost is noticeably lower than a biological treatment.

DESCRIPTION

30 The liquid waste from fish slaughtering activity is created from the slaughtering department, the blood drainage department and from the disinfection procedure of the areas.

The invention refers to the wet oxidation – sterilization of the wastes
35 from fish slaughtering by electrolysis where the conciseness of the liquid waste and sodium chloride is between 0,5% and 5% in weight/weight, the voltage of direct electric current is between 6V and 48V and the intensity of the direct electric current is between 50Amp and 500Amp. The temperature during electrolysis is between 14°C and 60°C and the pH
40 value between 2 and 9,5 points. For better results of oxidation-sterilization of the wastes, before they enter the electrolytic cell or the tank where the cell is, they passed from a fine grid, type screen or cylinder, spaced between 1mm to 0,01mm. The neutralization of the

residual oxidants is accessed by sodium sulfite, or sulfur dioxide assisted by redox meter.

EXAMPLE 1 (drawing 1)

5 50 liters of waste from fish slaughtering conciseness of 2% in sodium chloride are guided to screen (a) type cylinder with spacers 0,29mm to subtract any solid. The total volume is entering to the tank (b) 100lit capacity where a submersible pump (c) of re circulation 15m³/h driven
10 this to the electrolytic cell (d). Noble and strategic metals make the anode of the cell and stainless steel 316L the cathode. The cell (d), is powered by a DC transformer (e), with controlled voltage 0,5V to 48V and controlled intensity 0,5Amp to 500Amp. The waste water entering the cell (d) and re-circulated by the pump (c) is electrolyzed with a voltage
15 16V and an intensity of 100Amps for 60 minutes. The system has a thermal exchanging device (f), which keeps temperature below 60°C and especially to 30°C. The pH is maintained between 2 and 9,5 points and specially to 8,5 points by the support of a pH meter (g), which upon request adds oxide or base to the process from the tanks (h) or (i). At the
20 end of electrolysis, assisted by redox meter (j), the wastes are neutralized from the residual oxidants by addition of sulfur dioxide from tank (k).


EXAMPLE 2 (drawing 2)

25 50 liters of waste from fish slaughtering conciseness of 2% in sodium chloride are guided to screen (a) type cylinder with spacers 0,29mm to subtract any solid passing towards tank (b) of 100lit capacity. In tank (b) there is an electrolytic cell (c) witch noble and strategic metals make the anode of the cell and stainless steel 316L the cathode. The cell (c) is
30 powered by a DC transformer (d), with controlled voltage 0,5V to 48V and controlled intensity 0,5Amp to 500Amp. The liquid waste in tank (b) is electrolyzed for 60 minutes with a voltage 16V and an intensity of 100Amps. Through pH meter (f), I fix the value between 2 and 9,5 and especially to 4 points by addition of hydrochloric acid from tank (g). At
35 the end of electrolysis, assisted by redox meter (j), the wastes are neutralized from the residual oxidants by addition of sulfur dioxide from tank (k)


CLAIMS

1. Electrochemical method for wet oxidation – sterilization of liquid wastes from fish slaughtering, with controlled screen, controlled voltage and intensity direct electric current, controlled solution of sodium chloride in the waste, controlled temperature of liquid wastes during electrolysis, controlled value of pH during electrolysis and neutralizing residual oxidants by addition of sulfur dioxide, or sodium sulfite.
2. Electrochemical method for wet oxidation – sterilization of liquid wastes from fish slaughtering as claim 1 where the screen is made by a grid or cylinder with spacers between 1mm to 0,01mm.
3. Electrochemical method for wet oxidation – sterilization of liquid wastes from fish slaughtering as claim 1 where the voltage of the direct electric current is between 6V and 48V.
4. Electrochemical method for wet oxidation – sterilization of liquid wastes from fish slaughtering as claim 1 where the intensity of direct electric current is between 50Amp and 500Amp.
5. Electrochemical method for wet oxidation – sterilization of liquid wastes from fish slaughtering as claim 1 where the conciseness of sodium chloride is between 0,5 to 5% by weight/weight.
6. Electrochemical method for wet oxidation – sterilization of liquid wastes from fish slaughtering as claim 1 where the temperature, during electrolysis is between 14°C to 60°C.
7. Electrochemical method for wet oxidation – sterilization of liquid wastes from fish slaughtering as claim 1 where the pH value is between 2 and 9,5.
8. Electrochemical method for wet oxidation – sterilization of liquid wastes from fish slaughtering as claim 1 where the neutralization of residual oxidants is done by sodium sulfide.
9. Electrochemical method for wet oxidation – sterilization of liquid wastes from fish slaughtering as claim 1 where the neutralization of residual oxidants is done by sulfur dioxide.

DRAWING 1



DRAWING 2



INTERNATIONAL SEARCH REPORT

International Application No

PCT/GR 02/00053

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 C02F1/467 C02F1/461

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 C02F A61L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ, COMPENDEX

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	VIJAYARAGHAVAN K, RAMANUJAM T K, BALASUBRAMNIAN N: "In Situ Hypochlorous Acid generation for the Treatment of Distillery Spentwash" IND. ENG. CHEM. RES., vol. 38, 1999, pages 2264-2267, XP002229279 page 2264, right-hand column -page 2266, right-hand column; figure 1 ---	1-9
X	EP 1 074 515 A (STERILOX MEDICAL EUROP LTD) 7 February 2001 (2001-02-07) column 4, line 30 -column 6, line 8 column 23, line 35 -column 28, line 29 --- -/--	1

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- * & * document member of the same patent family

Date of the actual completion of the international search

30 January 2003

Date of mailing of the international search report

12/02/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Liebig, T

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GR 02/00053

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 1 108 683 A (SANYO ELECTRIC CO) 20 June 2001 (2001-06-20) page 10, line 1 -page 12, line 27 claims 1-4,8,16,19-23; figure 1 -----	1
A	LIN S H ET AL: "Saline wastewater treatment by electrochemical method" WATER RESEARCH, ELSEVIER SCIENCE PUBLISHERS, AMSTERDAM, NL, vol. 32, no. 4, 1 April 1998 (1998-04-01), pages 1059-1066, XP004116516 ISSN: 0043-1354 the whole document -----	1-9
A	DE 198 59 814 A (BUTZKE WERKE AQUA) 21 June 2000 (2000-06-21) the whole document -----	1-9
A	PATENT ABSTRACTS OF JAPAN vol. 1998, no. 14, 31 December 1998 (1998-12-31) & JP 10 249349 A (OGURA KOTARO;MATSUSHITA ELECTRIC IND CO LTD), 22 September 1998 (1998-09-22) abstract -----	1-9
A	RU 2 043 306 C (VSEROSSIJSKIJ NII MYASNOJ PROM) 10 September 1995 (1995-09-10) the whole document -----	1-9
A	WO 01 42143 A (GEMMA IND ECOLOGY LTD ;LIVSHITS DAVID (IL); CARDENAS RAUL C (US);) 14 June 2001 (2001-06-14) the whole document -----	1-9

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GR 02/00053

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 1074515	A	07-02-2001	EP 1074515 A2 GB 2352728 A , B	07-02-2001 07-02-2001
EP 1108683	A	20-06-2001	JP 2001170638 A JP 2001170642 A JP 2001219168 A JP 2001232364 A JP 2001293476 A CN 1299782 A EP 1108683 A2 US 2001004962 A1	26-06-2001 26-06-2001 14-08-2001 28-08-2001 23-10-2001 20-06-2001 20-06-2001 28-06-2001
DE 19859814	A	21-06-2000	DE 19859814 A1 EP 1024115 A2	21-06-2000 02-08-2000
JP 10249349	A	22-09-1998	NONE	
RU 2043306	C	10-09-1995	RU 2043306 C1	10-09-1995
WO 0142143	A	14-06-2001	AU 4517801 A WO 0142143 A2	18-06-2001 14-06-2001